



KEY FEATURES:

- Support USB-C and HDMI Input
- Compliant with HDCP 2.2 and Display Port 1.2a
- Video resolution up to 4K@60Hz
- Video bandwidth up to 18Gbps
- Auto and manual input switching
- Supports POC Function (Tx Powered by Rx)
- LPCM, Dolby Digital/Plus/Ex, Dolby True HD, DTS, DTS-HD Master Audio, DTS High Res, DSD
- US-One Gang enclosure for Decora style wall plate

CONNECTIVITY:

Transmitter:

Input	: 1 x HDMI (Type A, 19 Pin female)
	: 1 x USB Type-C (Female for AV)
	: 1 x USB Type-C (Female for Charging)
Output	: 1 x LAN (RJ45, 8-Pin, Female)

Receiver:

Input	: 1 x LAN (RJ45, 8-Pin, Female)
Output	: 1 x HDMI (Type A, 19 Pin female)
Control	: 1 x IR (3.5mm Stereo Mini-jack)
	: 1 x Service (Micro USB, Update Port)

COMPLIANCES:

HDMI Compliance	: HDMI 2.0b
HDCP Compliance	: HDCP 2.2
USB Type-C	: Display Port 1.2a

EXTENDING DISTANCE:

4K@60Hz	: 35 Meters / 115 Feet
4K@30Hz	: 50 Meters / 165 Feet

VIDEO OUTPUT :

Video Resolution	: Up to 4K@60Hz
Video Bandwidth	: 18Gbps (HDMI) & 5.4Gbps (USB Type-C)

ADDITIONAL FEATURES:

PoC/POE Function	: Yes
IP Control	: Yes
EDID	: Compatible

AUDIO SUPPORT :

HDMI Audio Formats : LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD

ENVIRONMENTAL:

Operating temperature:	: 0° to 50°C
Storage temperature	: -10° to 70°C
Humidity	: 10%~80% RH

POWER:

Power Supply	: Input AC 100-240V, Output: DC 12V/1A
Power Consumption	: TX : 3W (Max), RX : 3.72W (Max)

